

MULTIPLEXER FILTERS **PROFESSIONAL RANGE** | REFERENCES AND SPECIFICATIONS

References	858501	858502	858503	858504	858505	858506
Denomination	1 channel	2 channel	3 channel	4 channel	5 channel	6 channel
Frequency range	470 - 860 MHz					
Inpedance	50 Ω					
Number of cavities	3					
Input/output return losses	> 20 dB					
Bandwidth	1 TV Channel (CCIR 8 MHz)					
Insertion losses	2 dB					
Maximum input power	5 W DVB-T / 25 W analogue					
Channel N±3 rejection	> 25 dB					
Input connectors (up to 5)	BNC Female					
Output connector	BNC Female					
Size (width/height/depth)	45mm / 5HU / 250mm					



MULTIPLEXER FILTERS **BROADCAST RANGE** | REFERENCES AND SPECIFICATIONS

References	858508	858509	858510	858512	858511
Denomination	Diplexer	Triplexer	Tetraplexer	Pentaplexer	Double Diplexer
Frequency range	470 - 860 MHz				
Inpedance	50 Ω				
Number of cavities	3				
Input/output return losses	> 20 dB				
Bandwidth	1 TV Channel (CCIR 8 MHz)				
Insertion losses	1 dB				
Maximum input power	10 W DVB-T / 50 W analogue				
Channel N±3 rejection	> 30 dB				
Input connectors (up to 5)	BNC Female				
Output connector	Type N Female				
Size (width/height/depth)	19" / 3HU / 250mm				